# \*\*\*ILUFORMA PLAST



# ABOUT US:

Aluforma-Plast, the only one of its kind in Albania and the region in terms of modern technology, speed, high production capacity and quality, started its activity in 2023, with a serious investment that facilitated the introduction of the fully automatic line Elumatec and Someco in Albania

From 2023, Aluforma-Plast offers quality and speed to our customers in diverse projects such as residential complexes, accommodation facilities, and shopping centers, meeting global demands and setting high standards in the Albanian market and beyond.



Our mission is to transform the manufacturing industry with the maximum quality of aluminum and plastic production (facades, doors, windows, railings, shutters) using the most advanced German technology.

Quality.Precision.Speed – this is our motto, in order for our customers to always be one step ahead in time, quality and accuracy.



# VISION

Our vision is to lead the aluminum and plastic manufacturing sector by setting new standards for quality and sustainability in the market. We aim to be reliable partners for our customers, offering customized and unique solutions for their projects, thanks to the use of German technology and the latest practices in our field.

# **OUR PRODUCTS**

# **WINDOWS**

#### WINDOWS AND WINDOWS PANE WITH PVC

WINDOWS SYNEGO WINDOWS SYNEGO NL WINDOWS GENEO WINDOWS ARTEVO WINDOWS EURO-DESIGN 70

# **DOORS**

#### DOORS WITH PVC

EXTERIOR DOORS SYNEGOGUE SYNEGO SLIDING RAIL DOORS EXTERIOR DOORS BRILLIANT DESIGN

# **SHUTTERS**

#### SHUTTERS WITH PVC

EXAKT XT - THE RENOVATION SYSTEM
EXAKT XT - THE PROFI SYSTEM
ELITE XT - THE PREMIUM SYSTEM
NEO XT - THE SYSTEM FOR NEWBUILDS



# **PERGOLA**

#### **FACADES**

SMARTIA PG 160 P SANTORINI SMARTIA PG 115P ITHACA SMARTIA PG120F SMARTIA PG120P MYKONOS

# PARTITION SYSTEMS

#### **FENCES**

SMARTIA P100 SMARTIA P100 SLIM SMARTIA P150 URBAN SMARTIA P200 SMARTIA P200 SLIM P19 V-BLOCKER

# RAILINGS AND FENCES

#### **FENCES**

SMARTIA FC10 SMARTIA FC60 SMARTIA FC80 SMARTIA M8200 SMARTIA M8250

# QUALITY PRECISION SPEED



# **WINDOWS SYNEGO**

PVC SYSTEM WITH A DEPTH OF 80 MM AND UF VALUE UP TO 0.94 W/M<sup>2</sup>K

SYNEGO windows are the best solution for energy conscious customers. In addition to the Uf value of up to 0.94 W/m²K, the system has proven itself through the savings it offers and the multiple design variants.

# **TECHNICAL DATA**

The width of the bezel / headband	94mm to 175mm
Width of the locking mechanism	114mm to 218mm
The depth	80 mm
Number of rooms	7/6
Thickness	maximum 51 mm
Insulation systems	AD: 2 stop insulators MD: 2 stop insulators 1 central insulation
Profile design	Wing with offset surface, half arm with round arm

# **CHARACTERISTICS**

Thermal insulation Uf	up to 0.94 W/m²K
The value of acoustic insulation	Rw up to 47 dB
Resistance to theft (EN 1627)	up to RC3
Wind resistance (EN 12210)	B5
Impermeability to rain and wind (EN 12208)	9A
Air permeability (EN 12207)	4
Operators (EN 13115)	2





# WINDOWS SYNEGO NL

SYNEGO windows are in no way inferior to wooden windows, they even exceed them in terms of durability.

# **TECHNICAL DATA**

The width of the bezel / headband	119mm to 166mm for external doors
Width of the locking mechanism	164 mm
The depth	120 mm
Number of rooms	5/6
Thickness	51 mm
Insulation systems	1 locking stopper

# **CHARACTERISTICS**

Thermal insulation Uf	up to 1.0 W/m <sup>2</sup> K
The value of acoustic insulation	Rw up to 46 dB
Resistance to theft (EN 1627)	up to RC3
Wind resistance (EN 12210)	up to C5/B5
Impermeability to rain and wind (EN 12208)	up to 9A
Air permeability (EN 12207)	up to 4
Operators (EN 13115)	1





# **WINDOWS GENEO**

WINDOWS FOR A PERFECT HOME

GENEO windows come with the convincing advantage – in addition to excellent thermal insulation – of a comprehensive coordinated package. Because: Thanks to the RAU-FIPRO fiber composite material, GENEO offers maximum stability without steel content. GENEO windows are light and have thermal insulation properties that no other window can offer. Convince yourself!


#### **ADVANTAGES:**

Mund të kurseni energji deri në 76 %\*
Ndjehuni të sigurt falë sistemit të mbrojtjes nga hajdutët
Do të shijoni oazën tuaj të qetësisë përmes reduktimit 24-fish të zhurmës\*\*
Sa i përket dizajnit, imagjinata juaj nuk njeh kufij
Përjetoni një pastrim shumë të lehtë falë sipërfaqes së lëmuar
Të disponueshme edhe në versionin e certifikuar për shtëpi pasive
GENEO janë gjithashtu të disponueshme edhe si derë e jashtme edhe derë rrëshqitëse

\* Reduction of energy loss from windows in case you replace wooden/plastic windows from the 1980s (Uf = 1.9; Ug = 3.0) with GENEO profile windows (Uf = 0.89; Ug = 0.5), window dimensions 123 x 148 cm \*\* Basis of calculation: increase in noise level by 10 dB = twice the subjectively perceived sound volume (LfU). GENEO reduces noise by 47 d

### **RAU-FIPRO® - TECHNOLOGY FOR DEVELOPMENT**

Heat reduction Uw up to 0.61 W/m²K
Acoustic protection Rw = 47 dB
Theft resistance up to RC3
Construction depth 86 mm
6 rooms
Glass thickness up to 53 mm in the passive house certified version
Hermetic closure for the best possible protection from air currents and moisture
Air penetration 4
Rainfall density 9A
Wind resistance B5





PVC SYST



A revolutionary new premium system of window profiles, which sets new standards in the field of design, sizes, productivity and durability

#### **DESIGNED FOR OPTIMIZED PRODUCTION PROCESSES**

All ARTEVO components are designed for absolutely efficient and productive production:

- · Production of large elements is also possible without the use of steel reinforcement.
- · The 80mm platform strategy creates many beneficial synergies.
- · Profile geometry is optimized for connection technology.
- REHAU LowE foil can be integrated in the factory. But the application of the production process is very easy. The time-consuming use of thermal modules or foaming of profiles is no longer necessary.
- · Universal steel reinforcement for frame, arm and small invisible barrier.
- · With two steel wing reinforcements, no steel machining is required.

This reduces labor, time and costs.

#### **80MM PLATFORM STRATEGY**

The clever 80mm platform strategy massively reduces complexity and creates unimaginable freedom:

The same additional profiles as for SYNEGO Same formations for glass as for SYNEGO – for frame and arms Same floor sill as for SYNEGO

Universal steel reinforcements that facilitated processing.



# **WINDOWS EURO-DESIGN 70**

WINDOW SYSTEM WITH A DEPTH OF 70 MM

Our Euro-Design 70 window system offers your customers a wide range of design options. Thanks to the depth of 70 mm, it is also completely suitable for old buildings.

# **TECHNICAL DATA**

The depth	70 mm
Thermal insulation Uf	up to 1.3 W/m <sup>2</sup> K
The value of acoustic insulation	Rw up to 45 dB
Resistance to theft (EN 1627)	RC2

#### **YOUR ADVANTAGES:**

More storage space thanks to the same reinforcements for the frame and bar Available in all KALEIDO COLOR colors except KALEIDO VISION



# STRUCTURAL INSULATED WINDOW BAR

#### WINDOW BAR "L-THERM" BLACK-LINE

- Made of high density material thermoplastic foam, based on polystyrene
- Window bar L-THERM is suitable for thermal separation, for use in window or door profiles in commercial and residential projects to improve the energy efficiency of the building
- Minimize thermal bridging
- The surface is resistant to moisture
- Perfectly holds the load on windows
- The bars are easy and quick to install
- High compressive strength up to 25 kg/cm2
- An excellent thermal conductivity from 0.039 [W/m\*K]
- Density strength 150kg/m3
- Excellent water absorption capacity does not absorb more than 1.5% moisture







# **AIR TIGHTNESS**

# PENOSIL PREMIUM EXPANDING TAPE

It is especially designed as an external weather seal for facade joints and window frame joints directly exposed to very demanding weather conditions in buildings up to 100 m height.



# PENOSIL WINDOW & DOOR ELASTIC FOAM

PENOSIL Window & Door Elastic is a foam sealant for tight sealing of movable joints 1,5 x Better sound and thermal insulation Penosil Window & Door Elastic foam sealant's unique formula forms an exclusive "micro-cell" foam structure. This



# PENOSIL WINDOW TAPE FULL GLUE +1 INTERNAL

Penosil Window Tape Full Glue+1 Internal is a vapor barrier tape to cover window and door joints from inside. Prevents penetration of water vapor in the construction foam and wall structure. Ensures air tightness. Acrylic adhesive has excellent adhesion to all of the most common construction materials.



# **ACCESSORIES:**

#### **DOOR AND WINDOW LOCKS**

Locks provide security and functionality to systems. In the aluminum industry, the term "key" is mainly used for sliding doors and systems. In the two-position opening and lift&slide system, "Keys" are known as "mechanisms".



# HINGES OF DOORS AND WINDOWS

Hinges are a distinctive part of all opening systems. Depending on the requirements, hinges can have different characteristics.



#### **DOOR HANDLES AND WINDOWS**

The handles are the only point of contact with the aluminum system. The handle gives life to the rest of the system's accessories, which ensure its functionality. Thus, the Handle is a very important part of the system.



#### WINDOW AND DOOR MECHANISMS


Similar to what is discussed about locks, mechanisms provide security and functionality to a window or door. The main difference is that Locks are usually a single part, while mechanisms are a complete solution of several parts with a more complex function. There are 2 types of mechanisms, anti-bald opening, and lift & slide.



#### **OTHER ACCESSORIES**









# **SYNEGO EXTERIOR DOORS**

PROFILE SYSTEM WITH 80 MM DEPTH AND UDDERI VALUE OF 0.82 W/M²k

Designed for equipment with resistance class up to RC3, SYNEGO main doors offer excellent protection against forced entry. With thermal insulation, high acoustic insulation, durability and a wide range of colors, these main doors also meet the high demands of building owners.

#### **TECHNICAL DATA**

Width of the frame / frontal frame	174 mm
Frame depth	80 mm
Number of rooms	7/5
Thickness	maximum 51 mm
Profile design	Wing with offset surface

#### **CHARACTERISTICS**

Thermal insulation Uf	1,2 W/m²K
The value of acoustic insulation	Rw up to 45 dB
Resistance to theft (EN 1627)	up to RC2
Wind resistance (EN 12210)	B2
Impermeability to rain and wind (EN 12208)	4A
Air permeability (EN 12207)	4





OORS WIT

# **SYNEGO SLIDING RAIL DOORS**

PROFILE SYSTEM WITH A DEPTH OF 80 MM AND A UF VALUE OF UP TO 1.3 W/M<sup>2</sup>K

Like SYNEGO windows and front doors, the accompanying sliding rails also provide excellent protection against forced entry.

# **TECHNICAL DATA**

Width of the frame / frontal frame	103 mm
Frame depth	190 mm / 80 mm
Frame depth	5
Thickness	maximum 51 mm
Slide rail size	maximum 300 cm x 260 cm (W xH)
Profile design	Wing with offset surface

# **CHARACTERISTICS**

Thermal insulation Uf	1,30 W/m <sup>2</sup> K
The value of acoustic insulation	Rw up to 43 dB
Resistance to theft (EN 1627)	RC2
Wind resistance (EN 12210)	B3
Impermeability to rain and wind (EN 12208)	9A
Air permeability (EN 12207)	4





# **EXTERNAL DOORS BRILLANT DESIGN**

PROFILE SYSTEM WITH A DEPTH OF 70 MM AND BETTER RESISTANCE TO THEFT

Our brilliantly designed doors are particularly durable and long-lasting thanks to welded corner connections, rail-locked steel frame and high-volume reinforcements.

# **TECHNICAL DATA**

The width of the bezel / headband	166 mm
Width of the locking mechanism	128 mm (threshold height 20 mm)
The depth	70 mm
Number of rooms	5/4
Thickness	maximum 41 mm
Insulation systems	2 stop insulators
Profile design	Wing with offset surface

# **CHARACTERISTICS**

Thermal insulation Uf	1,6 W/m²K
The value of acoustic insulation	The value of acoustic insulation
Resistance to theft (EN 1627)	RC3
Wind resistance (EN 12210)	B2
Impermeability to rain and wind (EN 12208)	4A
Air permeability (EN 12207)	4







# **EXAKT XT**THE RENOVATION SYSTEM

EXAKT XT is EXTE's answer to the growing demand for space-saving and cost-effective solutions. This system is specifically designed for projects where compliance with size limits in accordance with GEG (Building Energy Act) is crucial.

# **ALL INFORMATION AT A GLANCE**

Intended Use	Renovation
Box Size	155 X 181   181 X 206   220 X 245
Revision Types	Innen
Hanging Types	Shutters, Screen
Hanging Heights	Mini: Tanks Up To 3,000 Mm Maxi: Tanks Up To 2,500 Mm
Guide Rails	35 X 51, 60 X 51 35 X 51, 60 X 51 (Internal Revision)
Sound Insulation Values	Up To 43 DB
Heat-Insulated	USB Up To 0.77 W/M2*K

# **EXAKT XT TYPES:**THE RENOVATION SYSTEM



CLASSIC ROLLER SHUTTER.


ELLE THE THE THE WEB



ZIP SCREEN. WITH FABRIC FOR



VENTO XT — THE EXHIBITION ROLLER SHUTTER.



LIFT-AND-SLIDE DOORS. VERY TRENDY.

# **ELITE XT** THE PREMIUM SYSTEM

With the EXTE ELITE XT, all designs can be realized with just one system platform. This opens up new business areas, for example through the use of external blinds and external auditing in the attachment box.

# **ALL INFORMATION AT A GLANCE**

ALL INFORMATION AT A C	
Intended Use	Renovation And New Construction
Box Size	75 X 220 I 200 X 220 I 240 X 220
	240 X 255 I 240 X 320
Revision Types	Inside, Below, Outside
Hanging Types	Shutters, Screens, Venetian Blinds
Hanging Heights	Mini: Tanks Up To 3,500 Mm
	Maxi: Tanks Up To 2,800 Mm
Guide Rails	35 X 51, 60 X 51 (Revision Bottom/Inner)
	35 X 86, 60 X 86 (External Revision)
	60 X 132 (External Blinds)
Sound Insulation Values	Up To 48 DB
Heat-Insulated	USB Up To 0.48 W/M2*K
	1 000
	1000

# **ELITE XT TYPES:** THE PREMIUM SYSTEM



CLASSIC ROLLER SHUTTER.


HH MH N




VENTO XT — THE EXHIBITION ROLLER SHUTTER.



ZIP SCREEN. WITH FABRIC FOR



INTEGRATED INSECT **PROTECTION** 



LIFT-AND-SLIDE DOORS. VERY TRENDY.



PERDE VENECIANE

# **EXPERT XT** THE PROFI SYSTEM

Me EXTE ELITE XT, të gjitha dizajnet mund të realizohen vetëm me një platformë sistemi. Kjo hap fusha të reja biznesi, për shembull nëpërmjet përdorimit të blindave të jashtme dhe auditimit të jashtëm në kutinë e bashkëngjitjes.

# **ALL INFORMATION AT A GLANCE**

Intended Use	Renovation And New Construction
Box Size	165 X 220 I 185 X 220 I 220 X 255
Revision Types	Inside, Below
Hanging Types	Shutters, Screen
Hanging Heights	Mini: Tanks Up To 3,500 Mm Maxi: Tanks Up To 2,800 Mm
Guide Rails	35 X 51, 60 X 51 (Revision Bottom/Inner) 60×35 (RUI35)
Sound Insulation Values	Up To 45 DB
Heat-Insulated	USB Up To 0.79 W/M2*K

# **EXPERT XT TYPES:**

THE PROFI SYSTEM



**CLASSIC ROLLER** SHUTTER.



ZIP SCREEN. WITH FABRIC FOR



**INTEGRATED INSECT PROTECTION** 



VENTO XT — THE EXHIBITION ROLLER SHUTTER.



LIFT-AND-SLIDE DOORS. VERY TRENDY.

# **NEO XT**THE SYSTEM FOR NEWBUILDS

The EXTE NEO XT represents the cutting edge of innovation at EXTE, specially developed to meet the demanding requirements of new buildings. It combines advanced technology with flexibility and efficiency to enable seamless integration into modern construction projects.

# **ALL INFORMATION AT A GLANCE**

Noubou
Neubau
250 X 240 I 260 X 270 (300, 365) I 290 X 270 (300, 365)
Below, Outside
Shutters, Screens, Venetian Blinds
Mini: Tanks Up To 3,900 Mm Maxi: Tanks Up To 2,850 Mm
35 X 51, 60 X 51, 60 X 35, (Revision Below) 35 X 86, 60 X 86 (External Revision) 60 X 132 (Venetian Blinds
Up To 46 DB
USB Up To 0.31 W/M2*K

# **NEO XT TYPES:**THE SYSTEM FOR NEWBUILDS




GRILA KLASIKE ME RUL.




VENTO XT GRILA E EKSPOZITËS ME RUL



EKRAN ZIP ME PËLHURË



DYERT ME NGRITJE DHE RRËSHQITJE.



MBROJTJE E INTEGRUAR NGA INSEKTET



PERDE VENECIANE



QUALITY PRECISION SPEED

# \*\*LUFORMA PLAST

Rruga Arbanes, Vaqarr, Tirana, Albania info@aluforma-plast.al management@aluforma-plast.al ofertime@aluforma-plast.al069

069 771 1111 069 302 2230 069 302 2260